



T644 Extra High Yield Print Cartridge

Printer: T644

Declaration of Yield:	Average Cartridge Yield	32000	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 34296
Std Dev 1163
90% Lower 33575
Confidence

For questions concerning testing contact:
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date tested	25-Mar-2005	30-Mar-2005
Number of cartridges in testing	9	
Qty. of cartridges used in calculation	9	
Shake Procedure	1st shake	At toner low
	2nd shake	At toner low
Print mode	Continuous	
Number of printers tested	3	
Media used	Boise Cascade - 20# - Letter	
Paper feed orientation	Short Edge Feed (SEF)	
Driver version	T644 version 1	
Operating system	Windows 2000	
Application software	Acrobat version 6.01	
Test page version	Down load Free__19752 Test Chart.pdf	

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAS050559299	PL2-1192-H	74	75	72	46	53	44	33,880	Y
CAS050559301	PL2-1191-H	74	75	72	46	53	44	33,120	Y
CAS050559297	PL2-1192-H	74	75	72	46	53	44	33,999	Y
CAS050559290	PL2-1191-H	74	75	72	46	53	44	35,399	Y
CAS050559304	PL2-1191-H	74	75	72	46	53	44	33,739	Y
CAS050559303	PL2-1190-H	74	75	72	46	53	44	35,560	Y
CAS050559285	PL2-1192-H	74	75	72	46	53	44	35,680	Y
CAS050559307	PL2-1190-H	74	75	72	46	53	44	34,921	Y
CAS050559327	PL2-1190-H	74	75	72	46	53	44	32,362	Y

Comments and or exceptions:
also covers:
64404XA 64416XE 64436XE
64404XE 64417XR 64437XR
64404XL 64418XL 64438XL
64404XR