

Optra M410/M412 Print Cartridge

Printer: Optra M412

Declaration of Yield:	Average Cartridge Yield	5000	standard pages
Declared yield value in accordance with ISO/IEC 19752			

Average 6518
Std Dev 354
90% Lower Confidence 6335

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date tested	22-Nov-2004	29-Nov-2004

Number of cartridges in testing	12
Qty. of cartridges used in calculation	12
Shake Procedure	1st shake At fade 2nd shake At fade
Print mode	Continuous
Number of printers tested	4
Media used	Boise Cascade X-9 - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	7.4.1
Operating system	Windows 2000
Application software	Adobe Acrobat version 6.01
Test page version	IS_19752_Testpage_Ver.200406.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAZ041120390	3030598	74	75	74	48	49	48	6,480	Y
CAZ041550300	3011999	74	75	74	48	49	48	6,041	Y
CAZ041920178	3028866	74	75	74	48	49	48	6,477	Y
CAZ041960635	3030179	74	75	74	48	49	48	6,542	Y
CAZ041960643	3030598	74	75	74	48	48	47	6,962	Y
CAZ041120328	3011999	74	75	74	48	48	47	6,243	Y
CAZ041550281	3028866	74	75	74	48	48	47	6,343	Y
CAZ041920167	3030179	74	75	74	48	48	47	6,531	Y
CAZ041920111	3030598	74	74	74	48	49	48	7,020	Y
CAZ041960626	3011999	74	74	74	48	49	48	7,042	Y
CAZ041120271	3028866	74	74	74	48	49	48	6,579	Y
CAZ041550316	3030179	74	74	74	48	49	48	5,960	Y

Comments and or exceptions:

