

T630, T632, T634 Print Cartridge

Printer: T632

Declaration of Yield: **Average Cartridge Yield 5000 standard pages**
Declared yield value in accordance with ISO/IEC 19752

Average 6205
Std Dev 728
90% Lower Confidence 5828

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested start 28-Sep-2004 stop 29-Sep-2004

Number of cartridges in testing	12
Qty. of cartridges used in calculation	12
Shake Procedure	1st shake At toner low
	2nd shake At toner low
Print mode	Continuous
Number of printers tested	4
Media used	Boise Cascade X-9 - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	8.4.0.0
Operating system	Windows 2000
Application software	Adobe Acrobat version 5.0
Test page version	Standard_Testpage_(PDF_1.3).pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAX042029097D	9912997	75	75	74	51	52	51	6,093	Y
CAX042067007D	99129B8	75	75	74	51	52	51	4,866	Y
CAX041658061D	99104KN	75	75	74	51	52	51	5,467	Y
CAX041637892D	99129B6	75	75	74	51	52	51	5,696	Y
CAX041637993D	9912997	75	75	75	51	51	51	7,529	Y
CAX042029573D	99129B8	75	75	75	51	51	51	6,993	Y
CAX042066336D	99104KN	75	75	75	51	51	51	5,907	Y
CAX041658066D	99129B6	75	75	75	51	51	51	5,993	Y
CAX041658075D	9912997	75	75	75	51	51	51	6,108	Y
CAX041637908D	99129B8	75	75	75	51	51	51	6,610	Y
CAX042028927D	99104KN	75	75	75	51	51	51	6,932	Y
CAX042066327D	99129B6	75	75	75	51	51	51	6,263	Y

Comments and or exceptions: