

**E210 Print Cartridge**

Printer: E210

Declaration of Yield: **Average Cartridge Yield 2000 standard pages**  
**Declared yield value in accordance with ISO/IEC 19752**

**Average** 2523  
**Std Dev** 67  
**90% Lower Confidence** 2482

**For questions concerning testing contact:**

Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

**Date tested**      start      stop  
 16-Aug-2004      18-Aug-2004

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake      At fade
Comment	2nd shake      At fade
Print mode	Continuous
Number of printers tested	3
Media used	Boise Cascade - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	4.11
Operating system	Windows 2000 Service Pack 4
Application software	Adobe Reader version 5.0
Test page version	IS 19752 Testpage.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
KRE1JC9602255AADUBX5Q0461	10-00109	74	74	74	53	55	52	2,571	Y
KRE1JC9602255AADUBX5Q0462	1038880	74	74	74	53	55	52	2,416	Y
KRE1JC9602255AADUBX5Q0502	10-00897	74	74	74	53	55	52	2,500	Y
KRE1JC9602255AADUBX5Q0113	10-00109	74	76	74	52	55	49	2,609	Y
B7LT100008	1038880	74	76	74	52	55	49	2,528	Y
B7LT100012	10-00897	74	76	74	52	55	49	2,589	Y
KRE1JC9602255AADUBX5Q0072	10-00109	74	75	74	51	51	50	2,531	Y
KRE1JC9602255AADUBX5Q0416	1038880	74	75	74	51	51	50	2,425	Y
KRE1JC9602255AADUBX5Q0426	10-00897	74	75	74	51	51	50	2,542	Y

**Comments and or exceptions:**