

E330, E332 High Yield Print Cartridge

Printer: E330/E332

Declaration of Yield:

Average Cartridge Yield	6000	standard pages
Declared yield value in accordance with ISO/IEC 19752		

Average 6760
Std Dev 438
90% Lower Confidence 6533

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested start stop
 12-Jan-2005 14-Jan-2005

Number of cartridges in testing	12
Qty. of cartridges used in calculation	12
Shake Procedure	1st shake At fade
	2nd shake At fade
Print mode	Continuous
Number of printers tested	4
Media used	Boise Cascade X-9 - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	9.3
Operating system	Windows 2000
Application software	Adobe Acrobat version 6.01
Test page version	IS_19752_Testpage_Ver.200406.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAX043502764	38031GP	73	74	73	51	51	51	6,979	Y
CAX043502776	380333Y	73	74	73	51	51	51	6,487	Y
CAX043512444	38031NB	73	74	73	51	51	51	7,227	Y
CAX043513990	38031NF	73	74	73	51	51	51	7,575	Y
CAX043512432	38031GP	73	73	73	51	51	50	6,775	Y
CAX043502760	380333Y	73	73	73	51	51	50	6,142	Y
CAX043502768	38031NB	73	73	73	51	51	50	6,302	Y
CAX043512436	38031NF	73	73	73	51	51	50	7,047	Y
CAX043512440	38031GP	73	73	73	51	51	51	6,913	Y
CAX143513943	380333Y	73	73	73	51	51	51	6,310	Y
CAX043502756	38031NB	73	73	73	51	51	51	6,373	Y
CAX043502797	38031NF	73	73	73	51	51	51	6,993	Y