

**T520/T522 Print Cartridge**

Printer: T522

Declaration of Yield: 

<b>Average Cartridge Yield</b>	<b>7500</b>	<b>standard pages</b>
<b>Declared yield value in accordance with ISO/IEC 19752</b>		

**Average** 8040  
**Std Dev** 365  
**90% Lower Confidence** 7851

**For questions concerning testing contact:**

Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

**Date tested**      start 29-Oct-2004      stop 31-Oct-2004

Number of cartridges in testing	12	At toner low
Qty. of cartridges used in calculation	12	At toner low
Shake Procedure	1st shake	Continuous
	2nd shake	
Print mode		4
Number of printers tested		Boise Cascade X-9 - 20# - Letter
Media used		Short Edge Feed (SEF)
Paper feed orientation		7.4.1
Driver version		Windows 2000
Operating system		Adobe Acrobat version 5
Application software		Standard_Testpage_(PDF_1.3).pdf
Test page version		

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAS041330258	9903G65	74	75	74	48	49	48	8,384	Y
CAX041744901	E004876	74	75	74	48	49	48	7,969	Y
CAS041402030	E004877	74	75	74	48	49	48	7,687	Y
CAS041530965	E004915	74	75	74	48	49	48	7,925	Y
CAX041745867	9903G65	74	74	74	48	48	48	7,806	Y
CAS041530949	E004876	74	74	74	48	48	48	7,615	Y
CAS041330245	E004877	74	74	74	48	48	48	8,762	Y
CAS041402027	E004915	74	74	74	48	48	48	8,001	Y
CAS041530944	9903G65	74	75	74	48	48	48	7,702	Y
CAS041402008	E004876	74	75	74	48	48	48	7,843	Y
CAX041744109	E004877	74	75	74	48	48	48	8,240	Y
CAS041330225	E004915	74	75	74	48	48	48	8,546	Y