



T640, T642, T644 High Yield Print Cartridge

Printer: T644

Declaration of Yield: **Average Cartridge Yield 21000 standard pages**
Declared yield value in accordance with ISO/IEC 19752

Average 24527
Std Dev 1551
90% Lower 23566
Confidence

For questions concerning testing contact:
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date tested	23-Mar-2005	31-Mar-2005
Number of cartridges in testing	9	
Qty. of cartridges used in calculation	9	
Shake Procedure	1st shake	At toner low
	2nd shake	At toner low
Print mode	Continuous	
Number of printers tested	3	
Media used	Boise Cascade - 20# - Letter	
Paper feed orientation	Short Edge Feed (SEF)	
Driver version	T644 version 1	
Operating system	Windows 2000	
Application software	Acrobat version 6.01	
Test page version	Down load Free__19752 Test Chart.pdf	

Cartridge testing data:	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
		Avg	Max	Min	Avg	Max	Min		
CAS050559216	PL2-1190-H	75	75	72	51	57	45	23,641	Y
CAS050559174	PL2-1190-H	75	75	72	51	57	45	26,039	Y
CAS050559215	PL2-1191-H	75	75	72	51	57	45	27,482	Y
CAS050559178	PL2-1191-H	75	75	72	51	57	45	24,820	Y
CAS050559276	PL2-1192-H	75	75	72	51	57	45	23,979	Y
CAS050559233	PL2-1192-H	75	75	72	51	57	45	24,862	Y
CAS050559193	PL2-1190-H	75	76	74	45	48	41	24,560	Y
CAS050559201	PL2-1191-H	75	76	74	45	48	41	22,440	Y
CAS050559185	PL2-1192-H	74	75	72	48	53	46	22,920	Y

Comments and or exceptions:

also covers:

64004HA	64016HE	64036HE
64004HE	64017HR	64037HR
64004HL	64018HL	64038HL
64004HR		