



T640, T642, T644 Print Cartridge

Printer: T644

Declaration of Yield: **Average Cartridge Yield 6000 standard pages**
Declared yield value in accordance with ISO/IEC 19752

Average 7298
Std Dev 264
90% Lower 7134
Confidence

For questions concerning testing contact:
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date tested	31-Mar-2005	1-Apr-2005
Number of cartridges in testing	9	
Qty. of cartridges used in calculation	9	
Shake Procedure	1st shake	At toner low
	2nd shake	At toner low
Print mode	Continuous	
Number of printers tested	3	
Media used	Boise Cascade - 20# - Letter	
Paper feed orientation	Short Edge Feed (SEF)	
Driver version	T644 version 1	
Operating system	Windows 2000	
Application software	Acrobat version 6.01	
Test page version	Down load Free__19752 Test Chart.pdf	

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAS050559091	PL2-1190-H	74	75	73	47	50	45	6,880	Y
CAS050559104	PL2-1191-H	74	75	73	47	50	45	7,180	Y
CAS050559131	PL2-1192-H	74	75	73	47	50	45	7,520	Y
CAS050559037	PL2-1192-H	74	75	73	47	50	45	7,519	Y
CAS050559084	PL2-1190-H	74	75	73	47	50	45	7,000	Y
CAS050559139	PL2-1191-H	74	75	73	47	50	45	7,640	Y
CAS050559021	PL2-1192-H	74	75	73	47	50	45	7,481	Y
CAS050559056	PL2-1190-H	74	75	73	47	50	45	7,340	Y
CAS050559089	PL2-1191-H	74	75	73	47	50	45	7,120	Y

Comments and or exceptions:

also covers:

64016SE	64036SE
64017SR	64037SR
64018SL	64038SL