

**W812 Print Cartridge**

Printer: W812

Declaration of Yield: **Average Cartridge Yield 12000 standard pages**  
**Declared yield value in accordance with ISO/IEC 19752**

**Average** 14410  
**Std Dev** 1405  
**90% Lower Confidence** 13539

**For questions concerning testing contact:**  
 Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

**start** **stop**  
**Date tested** 27-Sep-2004 29-Sep-2004

Number of cartridges in testing 9  
 Qty. of cartridges used in calculation 9  
 Shake Procedure 1st shake At toner low  
 2nd shake At toner low  
 Print mode Continuous  
 Number of printers tested 3  
 Media used Boise Cascade X-9 - 20# - Letter  
 Paper feed orientation Long Edge Feed (LEF)  
 Driver version W812 Printer Driver 8.0.1  
 Operating system Windows 2000 SP4  
 Application software Acrobat Reader Version 6.0.2  
 Test page version IS\_19752\_Testpage.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
ACT350172A044620047130	02-11162	72	74	70	51	57	48	13,380	Y
ACT350172A044220047130	02-10641	72	74	70	51	57	48	14,520	Y
ACT350172A045220047130	02-10726	72	74	70	51	57	48	13,810	Y
ACT350172A098320035080	02-11162	74	76	72	49	53	44	14,000	Y
ACT350172A045120047130	02-10726	74	76	72	49	53	44	13,540	Y
ACT350172A098420035080	02-10641	74	76	72	49	53	44	17,980	Y
ACT350172A031720047130	02-11162	75	76	75	47	49	44	13,860	Y
ACT350172A038520047130	02-10641	75	76	75	47	49	44	14,720	Y
ACT350172A039720047130	02-10726	75	76	75	47	49	44	13,880	Y

**Comments and or exceptions:**